

Features and Components

Use: A smooth cone-shaped boot, for traditional or split-pipe flashing applications to securely seal the penetration. Pipe boots eliminate the need for field fabrication.

Materials: Smooth, one-piece, molded TPO (thermoplastic polyolefin) cone-shaped boot with a preformed flange equipped with factory applied pressure sensitive tape.

Color: White



Component

A
Accessory

Single Ply

Type

FP
Penetration

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
Do not use in Multi-Ply systems								

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
Compatible with the selected Single Ply systems above							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Self-Adhered

- Prime TPO membrane with JM TPO Membrane Primer or JM Single Ply Membrane Primer (Low VOC) before applying JM TPO Pipe Boots (Peel and Stick).
- Do not install JM TPO Pipe Boots (Peel and Stick) in direct contact with asphalt.
- Refer to JM TPO applicator guides or detail drawings for instructions.

Packaging and Dimensions

Size	1" to 6" (2.54 cm to 15.24 cm)
Boots & Clamps / Box	10
Weight per Boot	0.93 lb (0.42 kg)
Weight per Box	10 lb (4.5 kg)

Storage

Shelf Life	18 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.