

Features and Components

Use: A prefabricated, reinforced 60 mil JM TPO, square boot in 2" and 4" (5.08 cm and 10.16 cm) sizes for tube-flashing application. Pipe boots minimize the need for field fabrication. Custom sizes and colors are available upon request. Contact your JM representative for minimum order quantity and lead time.

Material: JM TPO 60 mil reinforced membrane, with one of the widest welding windows, that is factory fabricated into a one-piece square split-pipe boot.

Color: White



Component

A
Accessory

Single Ply

Type

FP
Penetration

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
<i>Do not use in Multi-Ply systems</i>								

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
<i>Compatible with the selected Single Ply systems above</i>							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Energy and the Environment

Standard		Reflectivity	Emissivity
CRRC®	Initial	0.77	0.87
	3 Yr. Aged	0.70	0.86
CA Title 24	Pass	0.77	0.87
ENERGY STAR®	Initial	0.78	0.87
	3 Yr. Aged	0.68	
LEED® (SRI)	Initial	101	
	3 Yr. Aged	85	
Recycled Content	Post-consumer	0%	
	Post-industrial	5%	

The LEED® Solar Reflectance Index (SRI) is calculated per ASTM E1980.

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Hot Air Weld

- Do not install JM TPO Split Square Pipe Boots in direct contact with asphalt or coal tar pitch.
- Refer to JM TPO application guides or detail drawings for instructions.

Packaging and Dimensions

Size/Round Base	2" (5.08 cm) – 16" (40.64 cm) Base 4" (10.16 cm) – 16" (40.64 cm) Base
Height	8" (20.32 cm)
Boots per Box	8
Weight per Box	2" – 7 lb (3.18 kg) 4" – 8.7 lb (3.95 kg)