

Features and Components

Use: Fabricated by the contractor into metal flashings and edge details. It is used to provide monolithic water-tight protection for both adhered and mechanically fastened roofing assemblies.

Materials: 30 mil (0.76 mm) UV-resistant TPO (thermoplastic polyolefin) membrane laminated to .040 aluminum.

Color: White



Component

A
Accessory

Single Ply

Type

FE
Flashing Edge

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
Do not use in Multi-Ply systems									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
Compatible with the selected Single Ply systems above							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Mechanically Fastened



Hot Air Weld (for membrane)

- Do not install in direct contact with asphalt, coal tar pitch, or any petroleum-based product.
- Refer to JM TPO applicator guides or detail drawings for instructions.

Packaging and Dimensions

Sheet Size	4' x 10' (1.22 m x 3.05 m)
Nominal Thickness:	
Membrane	0.030" (0.76 mm)
Metal	0.040" (1.02 mm)
Total	0.070" (1.78 mm)
Sheets per Pallet	30
Coverage per Pallet	1,200 ft ² (111.5 m ²) (gross)
Weight per Sheet	27 lb (12.2 kg)
Weight per Pallet	995 lb (451 kg)

Storage

Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application. Store flat, not on end, protected from warping, bending or contamination.
--------------------	---