

MINIMUM BOARD ATTACHMENT PATTERNS

To Qualify for a 55 mph JM Peak Advantage® Guarantee (max. 20 year term)

The following requirements represent the minimum fastener and plate attachment criteria to qualify for a 55 mph JM Peak Advantage Guarantee up to a 20 year term, and buildings less than or equal to 60' in height. This information does not represent compliance with applicable building codes, FM requirements, guarantees above 55 mph and/or greater than 20 years, or buildings greater than 60' in height. For compliance with specific wind uplift criteria and systems beyond a standard 20 year Peak Advantage Guarantee, please contact JM Technical Services at 1-800-922-5922 Option 3.

These attachment rates apply with the following deck types: min. 22 ga steel, structural concrete, min. 5/8" plywood, and wood plank. Contact JM Technical Services for fastening rates into decks not listed, such as LWIC, Cementitious Wood Fiber, Gypsum, Metal Roof Panels, 1/2"plywood, and OSB decks.

*Special Fastening Layout 1 One-Sided Asphalt Application Only, No Encapsulation 2 TPO & PVC Membranes Only, No EPDM 3 JM QuickFoam Only Over Steel Deck with 1st Board Fastened 4 Limited to a Max 2.6" Thickness

Board Type	Board Product	Board Thickness	
Polyiso Insulation (20 or 25psi)	ENRGY 3	1"	
	ENRGY 3	1.1"- 1.4"	
	ENRGY 3	1.5"-1.9"	
	ENRGY 3	>2"	
	ENRGY 3 - Tapered	Varies	
	ENRGY 3 CGF	1"	
	ENRGY 3 CGF	1.1"- 1.4"	
	ENRGY 3 CGF	1.5"-1.9"	
	ENRGY 3 CGF	>2"	
	ENRGY 3 CGF - Tapered	Varies	
	ProtectoR Foam	Varies	
ards	ProtectoR HD	1/2"	
/er Bo	SeparatoR CGF	1/2"	
Polyiso Cover Boards	SeparatoR	1/2"	
Polyi	ENRGY 3 HD	1/2"	
	DEXcell FA Glass Mat Roof Board	1/4"	
	DEXcell FA Glass Mat Roof Board	1/2"	
	DEXcell FA Glass Mat Roof Board	5/8"	
	DEXcell Glass Mat Roof Board	1/4"	
	DEXcell Glass Mat Roof Board	1/2"	
	DEXcell Glass Mat Roof Board	5/8"	
	DEXcell FA VSH Glass Mat Roof Board	5/8"	
	DensDeck Prime Roof Board	1/4"	
oards	DensDeck Prime Roof Board	1/2"	
Gypsum Cover Boards	DensDeck Prime Roof Board	5/8"	
S) HI	DensDeck Roof Board	1/4"	
Gypsı	DensDeck Roof Board	1/2"	
	DensDeck Roof Board	5/8"	
	DensDeck StormX Prime Roof Board	5/8"	
	SECUROCK Gypsum-Fiber Roof Board	1/4"	
	SECUROCK Gypsum-Fiber Roof Board	1/2"	
	SECUROCK Gypsum-Fiber Roof Board	5/8"	
	SECUROCK Ultralight Glass-Mat Roof Board	1/4"	
	SECUROCK Ultralight Glass-Mat Roof Board	1/2"	
	SECUROCK Ultralight Glass-Mat Roof Board	5/8"	
nent	DEXcell Cement Roof Board	7/16"	
Cemen	SECUROCK Cement Roof Board	1/2"	
	DuraBoard	1/2-1"	
ards	JM FESCO Board	3/4-2"	
/er Bo	JM FESCO Board HD	1"	
Perlite Cover Boards	1/2" Retro-Fit™ Board	1/2"	
Perli	RetroPlus™ Roof Board	1/2"	
	Tapered FESCO Board	Varies	
ned	Fiberglass Reinforced		
Fastened Base Sheet	Polyester or Composite Reinforced		
ш			

MECHANICALLY FASTENED MEMBRANE							
Single Pl		Single Pl		Bituminous			
Preliminary Fastened		RhinoBond Grid Pattern		Preliminary			
4x4 4x8 Board Board		4x4 Board	4x8 Board	Fastened 4x4 Board	4x8 Board		
4	5	4	6	4	5		
4	5	4	6	4	5		
4	5	4	6	4	5		
4	5	4	6	4	5		
4		4		4			
4	5	4	6	4	5		
4	5	4	6	4	5		
4	5	4	6	4	5		
4	5	4	6	4	5		
4		4		4			
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
*4	*8	5	9	4	*8		
*4	*8	5	9	4	*8		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	4	4	6	4	4		
4	5	4	6	4	4		
4	5	4	6	4	4		
4	5			4	5		
4				4			
Tack in P	lace as Ne	eded]		

Tack in Place as Needed


ADHERED MEMB Single Ply		Bitumino	nus	Single F	'lv	Bitumin	וחווג	Single Ply		Bituminous	
Fastened		Fastene		Ribbon	<u>'</u>	Ribbon		Asphalt or		Asphalt or	
lx4	4x8	4x4	4x8	Adhered 4x4	4x8 Board	Adhered 4x4	4x8 Board	Spatter 4x4	4x8	Spatter 4x4	4x8
Board B	Board 16	Board 8	Board 16	Board 12"oc	Board	Board 12"oc	Board	Board	Board	Board	Board
			_					coverage		coverage	
}	16	8	16	12"oc		12"oc		coverage		coverage	
i	12	4	8	12"oc	12"oc3	12"oc	12"oc3	full coverage		full coverage	
1	8	4	8	12"oc	12"oc³	12"oc	12"oc3	full coverage		full coverage	
3		8		12"oc		12"oc		full coverage		full coverage	
3	16	8	16	12"oc		12"oc		full coverage		full coverage	
3	16	8	16	12"oc		12"oc		full coverage		full coverage	
6	12	4	8	12"oc	12"oc3	12"oc	12"oc3	full coverage		full coverage	
ļ	8	4	8	12"oc	12"oc ^{3/4}	12"oc	12"oc3/4	full coverage		full coverage	
3		8		12"oc		12"oc		full		full	
1	*8	4	*8	12"oc	12"oc3	12"oc	12"oc3	coverage		coverage	
	*8	4	*8	+			12"oc3	full		full	
4	-		-	12"oc	12"oc³	12″oc		coverage ¹		coverage ¹	
4	*8	4	*8	12"oc	12"oc³	12"oc	12"oc³				
								6.11		()	
5	10	4	8	12"oc	12"oc3	12"oc	12"oc3	full coverage		full coverage	
1	8	4	8	12"oc	12"oc3	12"oc	12"oc3	full coverage		full coverage	
1	6	4	6	12"oc	12"oc3	12"oc	12"oc3	full coverage		full coverage	
1	8	4	6	12"oc	12"oc3	12"oc	12"oc3	full		full	
5	10	4	8	12"oc	12"oc3	12"oc	12"oc3	coverage full		coverage full	
	8	4	8	_	_		_	full		full	
4				12"oc	12"oc³	12"oc	12"oc³	coverage		coverage	
1	6	4	6	12"oc	12"oc3	12"oc	12"oc3	coverage		coverage	
1	8	4	6	12"oc	12"oc3	12"oc	12"oc3	full coverage		full coverage	
5	10			12"oc	12"oc3		12"oc3	full coverage ²			
1	8	4	8	12"oc	12"oc3	12"oc	12"oc3	full coverage		full coverage	
1	6	4	6	12"oc	12"oc3	12"oc	12"oc3	full		full	
								coverage		coverage	
	0	4	0	10"		10"					
1	8	4	8	12"oc		12"oc					
1	8	4	8	12"oc		12"oc		full		full	
		8		12"oc		12"oc		coverage		coverage	
		8		12"oc		12"oc		full coverage		full coverage	
		4		12"oc		12"oc		full coverage		full coverage	
		8	16	12"oc		12"oc		full coverage		full coverage	
3	16	8	16	12"oc		12"oc		full coverage		full coverage	
		8						full coverage		full coverage	
			1			1		, 50.0.ugo			


Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy for general educational purposes only. This complimentary assistance is not to be either used or relied upon by anyone as a substitute for professional engineering design and documentation required by any building code, contract, or applicable law. By accepting the general conceptual information, you agree it does not constitute any representations, endorsements of, or an assumption by Johns Manville of any duty or liability for either the adequacy of the design of a building, any of its components or the sufficiency of any construction.




























(Steel N-Deck Specific)




































































































(Standard Deck)






















(Steel N-Deck Specific)













































(Standard Deck)








































(Steel N-Deck Specific)


$4' \times 8'$ (1.22 m \times 2.44 m) Boards



























12 FASTENERS / BD.


4' x 4' (1.22 m x 1.22 m) Boards





14 FASTENERS / BD.


16 FASTENERS / BD.









































24"


0


14 FASTENERS / BD.


4' x 8' (1.22 m x 2.44 m) Boards





12 FASTENERS / BD.












































14 FASTENERS / BD.





4' x 8' (1.22 m x 2.44 m) Boards





12 FASTENERS / BD.























RIBBON ADHERED — PACKAGING: DRUM / BOX / CARTRIDGE


(3/4" Bead Width - With Return)


















(1-1/4" Bead Width - Strait Line)















RIBBON ADHERED — PACKAGING: DRUM / BOX / CARTRIDGE


(3/4" Bead Width - With Return)


4' x 8' (1.22 m x 2.44 m) Boards


LIMITED TO JM QUICKFOAM ONLY FOR 1.5"-2.6" ENRGY 3 PRODUCTS, PROTECTOR HD, SEPARATOR CGF, AND PRIMED GYPSUM BOARDS OVER STEEL DECKS WITH THE FIRST BOARD FASTENED













RIBBON ADHERED — PACKAGING: CANISTER

(1-1/4" Bead Width - Strait Line)

4' x 8' (1.22 m x 2.44 m) Boards

LIMITED TO JM QUICKFOAM ONLY FOR 1.5"-2.6" ENRGY 3 PRODUCTS, PROTECTOR HD, SEPARATOR CGF, AND PRIMED GYPSUM BOARDS OVER STEEL DECKS WITH THE FIRST BOARD FASTENED

