



**NOTES:**

1. REFER TO JOHNS MANVILLE WEBSITE ([www.jm.com](http://www.jm.com)) FOR MOST UP-TO-DATE INFORMATION.
2. ANY CARPENTRY, METAL WORK, OR MASONRY CONSTRUCTION SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL.
3. PLEASE SEE BITUMINOUS APPLICATION GUIDES FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.
4. USE OVER SMOOTH OR MINERAL-SURFACED ROOFS, OR PRIOR TO GRAVELING.
5. ALL FOUR CORNERS OF THE PAD SHOULD BE FULLY AND FIRMLY SET PRIOR TO WALKING ON.

DRAWING NO.

**BIT-PT-04**

PROTECTION

**DYNATRED TRAFFIC PADS WITH PAVERS**

MEMBRANE TYPE:  
MODIFIED BITUMINOUS

MAXIMUM GUARANTEE TERM:  
30 YEAR

SCALE  
N.T.S

ISSUE DATE  
11-18-22

Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy for general educational purposes only. This complimentary assistance is not to be either used or relied upon by anyone as a substitute for professional engineering design and documentation required by any building code, contract, or applicable law. By accepting the general conceptual information, you agree it does not constitute any representations, endorsements of, or an assumption by Johns Manville of any duty or liability for either the adequacy of the design of a building, any of its components or the sufficiency of any construction.

