



JM EPDM 6" REINFORCED TERMINATION STRIP (RTS)

ALIGN MEMBRANE EDGES SO THAT SEAM TAPE HAS ~1/8" EXPOSURE

FACTORY INSEAM TAPE (FIT)

JM SINGLE PLY PRIMER APPLIED TO MEMBRANE SURFACE (NOTE 4)

JM APPROVED FASTENER AND PLATE 12" O.C. MAXIMUM PENETRATION DEPENDANT ON DECK MATERIAL(S). SEE SPECIFICATIONS FOR FURTHER INFORMATION

NOTES:

1. REFER TO JOHNS MANVILLE WEBSITE (www.jm.com) FOR MOST UP-TO-DATE INFORMATION.
2. PLEASE SEE SINGLE PLY FLASHING SPECIFICATIONS FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.
3. ANY CARPENTRY OR METAL WORK SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL.
4. JM EPDM TAPE PRIMER OR JM SINGLE PLY MEMBRANE PRIMER (LOW VOC) MUST BE APPLIED ON ALL MEMBRANE SURFACES COMING INTO CONTACT WITH JM EPDM PEEL & STICK PRODUCTS. ROLL MEMBRANE WITH HAND ROLLER UNDER PRESSURE AT SEAM IN ACCORDANCE WITH THE JM EPDM INSTALLATION GUIDE.
5. FOR JM APPROVED TOP OF WALL FLASHING METHODS SEE E-FW-E DETAILS.
6. ALL EDGES WITH EXPOSED JM EPDM SELF ADHERED ADHESIVE MUST BE STRIPPED IN.
7. FOR VERTICAL OSB APPLICATIONS IN TEMPERATURE RANGES BETWEEN 20°F AND 40°F, JM ALL SEASON SPRAYABLE BONDING ADHESIVE, JM SA PRIMER, OR JM SA PRIMER LVOC IS NEEDED. FOR APPROVED SUBSTRATES WITH A POROUS AND ROUGH SURFACE INCLUDING CONCRETE AND SMOOTH FACED CMU, PRIME WITH JM ALL SEASON SPRAYABLE BONDING ADHESIVE, SA PRIMER, OR SA PRIMER LVOC PRIOR TO INSTALLATION OF MEMBRANE. THE SAME ADHESIVE USED ON THE VERTICAL SUBSTRATE CAN BE USED CONTINUOUSLY THROUGH THE TRANSITION OF THE E-FW-B BASE FLASHING DETAILS.

DRAWING NO.

E-FW-M3I

FLASHING WALL

JM EPDM SELF ADHERED CONTINUOUS WALL FLASHING

MEMBRANE TYPE:
JM EPDM SA

MAXIMUM GUARANTEE TERM:
25 YEAR

SCALE: N.T.S.
ISSUE DATE: 01-28-25

Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy for general educational purposes only. This complimentary assistance is not to be either used or relied upon by anyone as a substitute for professional engineering design and documentation required by any building code, contract, or applicable law. By accepting the general conceptual information, you agree it does not constitute any representations, endorsements of, or an assumption by Johns Manville of any duty or liability for either the adequacy of the design of a building, any of its components or the sufficiency of any construction.

