


ROLL PATCHES INTO SEAMS WITH
HAND ROLLER UNDER PRESSURE
AND CREASE INTO SEAMS
ACCORDING TO THE JM PVC
APPLICATION GUIDE

JM SINGLE PLY LVOC
CAULK UNDER THE PATCH
AT T-JOINT INTERSECTION
RECOMMENDED

JM PVC
T-JOINT PATCH

1 1/2" (38mm) MIN.
WELD CONTINUOUS

JM SINGLE PLY LVOC CAULK ALL
AROUND T-JOINT PATCH




ISOMETRIC VIEW T-JOINT

JM PVC MEMBRANE ADHERED
OR MECHANICALLY FASTENED

JM PVC MEMBRANE
ADHESIVE (FOR ADHERED
SPECIFICATIONS ONLY)

1 1/2" (38 mm) MIN. WELD
(CONTINUOUS)



NOTES:

1. REFER TO JOHNS MANVILLE WEBSITE (www.jm.com) FOR MOST UP-TO-DATE INFORMATION.
2. PLEASE SEE SINGLE PLY FLASHING SPECIFICATIONS FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.
3. ANY CARPENTRY OR METAL WORK SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL.
4. JM PVC EDGE SEALANT IS OPTIONAL ON ALL CUT OR NON-ENCAPSULATED EDGES OF REINFORCED MEMBRANE. THIS INCLUDES FACTORY CUT MEMBRANE (SEE DETAIL P-MS-01).

DRAWING NO.

P-MS-17

MBR SEAMING

PVC T-JOINT PATCH

MEMBRANE TYPE:
JM PVC

SCALE
N.T.S

ISSUE DATE
08-07-19

MAXIMUM GUARANTEE TERM:
30 YEAR

Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy. This complimentary assistance is not to be used or relied upon by anyone as a substitute for professional engineering design and documentation required by building code, contract, or applicable law. By accepting these comments you agree they do not constitute any representations, endorsements of, or an assumption by Johns Manville of any liability for either the adequacy of the design of this building or any other material not supplied by Johns Manville.

