



4" (102 mm)
SEE PRODUCT CUT SHEET
ON JM WEBSITE

APPROVED
WALL / SUBSTRATE

APPROVED DECK

JM INSULATION/
COVER BOARD

JOINT WIDTH

JM APPROVED FASTENER AND PLATE 12" (304 mm) O.C. MAX.
PENETRATION DEPENDANT ON DECK MATERIAL(S).
SEE SPECIFICATIONS FOR FURTHER INFORMATION

INTEGRAL VAPOR BARRIER
INSULATION SUPPORT (OPTIONAL)
FIBER GLASS BATT INSULATION
IN POLY SLEEVE (OPTIONAL)

NOTES:

1. REFER TO JOHNS MANVILLE WEBSITE (www.jm.com) FOR MOST UP-TO-DATE INFORMATION AND INSTALLATION INSTRUCTIONS.
2. PLEASE SEE SINGLE PLY FLASHING SPECIFICATIONS FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.
3. ANY CARPENTRY OR METAL WORK SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL.
4. JM TPO MEMBRANE PRIMER OR JM SINGLE PLY MEMBRANE PRIMER (LOW VOC) MUST BE APPLIED TO ALL SURFACES COMING INTO CONTACT WITH JM TPO COVER TAPE. ROLL TAPE WITH HAND ROLLER UNDER PRESSURE.

DRAWING NO.		EXPAND-O-FLASH ROOF TO WALL (STYLE EJ)		
T-EJ-04				
NEW DETAIL		MEMBRANE TYPE:	Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy. This complimentary assistance is not to be used or relied upon by anyone as a substitute for professional engineering design and documentation required by building code, contract, or applicable law. By accepting these comments you agree they do not constitute any representations, endorsements of, or an assumption by Johns Manville of any liability for either the adequacy of the design of this building or any other material not supplied by Johns Manville.	
		TPO		
SCALE	ISSUE DATE	MAXIMUM GUARANTEE TERM:		
N.T.S	10-08-18	20 YEAR		