



EXISTING BITUMINOUS SUBSTRATE

EXISTING METAL GRAVEL STOP

CONTINUOUS CLEAT PER SMACNA OR NRCA

WOOD NAILERS FASTENED AS REQUIRED

JM COATING SILICONE FIELD SYSTEM (NOTE 4)

JM COATING POLYESTER REINFORCING FABRIC

JM COATING UNIVERSAL BASE

6" MIN.

EXISTING MODIFIED BITUMINOUS SUBSTRATE BELOW FIELD SYSTEM

JM COATING REPAIR TAPE (6" MIN.)

INSULATION/COVER BOARD

EXISTING DECK

**NOTES:**

1. REFER TO JOHNS MANVILLE WEBSITE ([www.jm.com](http://www.jm.com)) FOR MOST UP-TO-DATE INFORMATION.
2. ANY CARPENTRY, METAL WORK, OR MASONRY CONSTRUCTION SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL.
3. JM COATING FLASHING CONSISTS OF JM COATING REPAIR TAPE.
4. FOR JM COATING SILICONE FIELD SYSTEM 5 AND 10 YEAR GUARANTEE TERMS, USE THE APPROPRIATE APPLICATION REQUIREMENTS. REFER TO JM COATING SPECIFICATIONS FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.

DRAWING NO.  
**CS-FE-01**

**METAL EDGE FLASHING**

MEMBRANE TYPE:  
JM COATING - SILICONE

SCALE  
N.T.S

ISSUE DATE  
01-23-19

MAXIMUM GUARANTEE TERM:

Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy. This complimentary assistance is not to be used or relied upon by anyone as a substitute for professional engineering design and documentation required by building code, contract, or applicable law. By accepting these comments you agree they do not constitute any representations, endorsements of, or an assumption by Johns Manville of any liability for either the adequacy of the design of this building or any other material not supplied by Johns Manville.

