



Product	Use			Reinforcement		Application		ASTM	Roll Coverage*
	Base	Ply	Cap	Fiber Glass	Composite	Hot Asphalt 	Mechanically Fastened 		
<b>GlasBase® Plus</b>	X	X		X		X	X	D 4601, Type II	319 ft <sup>2</sup> (29.64 m <sup>2</sup> )
<b>GlasKap®</b>			X	X		X		D 3909	101 ft <sup>2</sup> (9.38 m <sup>2</sup> )
<b>GlasKap® CR G</b>			X	X		X		D 3909	101 ft <sup>2</sup> (9.38 m <sup>2</sup> )
<b>GlasKap® Plus</b>			X	X		X		D 3909	107 ft <sup>2</sup> (9.9 m <sup>2</sup> )
<b>GlasPly® IV</b>		X		X		X		D 2178, Type IV	531 ft <sup>2</sup> (49.33 m <sup>2</sup> )
<b>GlasPly® Premier</b>		X		X		X		D 2178, Type VI	531 ft <sup>2</sup> (49.33 m <sup>2</sup> )
<b>GlasTite® Flexible</b>	X	X			X	X	X	D 4601, Type II	150 ft <sup>2</sup> (13.94 m <sup>2</sup> )
<b>PermaPly® 28</b>	X	X		X		X	X	D 4601, Type II	300 ft <sup>2</sup> (27.87 m <sup>2</sup> )
<b>Ventsulation® Felt</b>	X			X			X	D 4897, Type II	100 ft <sup>2</sup> (9.3 m <sup>2</sup> )

\*Roll Coverage, can assume a 2" side lap and 4" end lap for some products. Please refer to product Data Sheets.