











| Product | Use | | | | | Reinforcement | | | Application | | | | | ASTM | Size |
|-----------------------|------|-----|-----|----------|------------|---------------|-----------|-----------|--|--|---|--|--|-------------------------|---|
| | Base | Ply | Cap | Flashing | Protection | Fiber Glass | Polyester | Composite | Hot Asphalt  | Cold Adhesive  | Heat Weld  | Self-Adhering  | Mechanically Fastened  | | |
| DynaBase® | X | | | | | X | | | X | X | | | | D 6163, Type I, Grade S | 150 ft ² (13.94 m ²) |
| DynaClad® | | | | X | | X | | | X | X | | | | D 6298 | 100 ft ² (9.29 m ²) |
| DynaClad® Copper | | | | X | | X | | | X | X | | | | D 6298 | 100 ft ² (9.29 m ²) |
| DynaGlas® | | | X | | | X | | | X | X | | | | D 6163 Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaGlas® FR | | | X | | | X | | | X | X | | | | D 6163 Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaGlas® FR CR | | | X | | | X | | | X | X | | | | D 6163 Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaGlas® 30 FR | | | X | | | X | | | X | X | | | | D 6163 Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaLastic® 180 S | X | | | | | | X | | X | X | | | X | D 6164 Type I, Grade S | 100 ft ² (9.29 m ²) |
| DynaBase® PR | X | | | | | | X | | X | X | | | X | D 6164 Type I, Grade S | 150 ft ² (13.94 m ²) |
| DynaLastic® 180 | | | X | | | | X | | X | X | | | | D 6164 Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaLastic® 180 FR | | | X | | | | X | | X | X | | | | D 6164 Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaLastic® 180 FR CR | | | X | | | | X | | X | X | | | | D 6164 Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaLastic® 250 | | | X | | | | X | | X | X | | | | D 6164 Type II, Grade G | 100 ft ² (9.29 m ²) |
| DynaLastic® 250 FR | | | X | | | | X | | X | X | | | | D 6164 Type II, Grade G | 100 ft ² (9.29 m ²) |
| DynaLastic® 250 FR CR | | | X | | | | X | | X | X | | | | D 6164 Type II, Grade G | 100 ft ² (9.29 m ²) |
| DynaPly® T1 | X | | | | | | | X | X | X | | | | D 6162 Type I, Grade S | 100 ft ² (9.29 m ²) |
| DynaFlex® | | | | X | | | X | | X | X | | | | D 6221 Type I | 75 ft ² (6.98 m ²) |
| DynaFlex® CR | | | | X | | | X | | X | X | | | | D 6221 Type I | 75 ft ² (6.98 m ²) |
| DynaKap® T1 | | | X | | | | X | | X | X | | | | D 6162 Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaKap® FR T1 | | | X | | | | X | | X | X | | | | D 6162 Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaKap® FR T1 CR | | | X | | | | X | | X | X | | | | D 6162 Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaTred™ | | | | | X | | | | X | X | | | | NA | |
| DynaTred™ Plus | | | | | X | | | | X | X | | | | NA | |
| DynaBase® HW | X | | | | | X | | | | | X | | | D 6163, Type I, Grade S | 150 ft ² (13.94 m ²) |



SBS Modified Bitumen Membrane Selector Guide

| Product | Use | | | | | Reinforcement | | | Application | | | | | ASTM | Size |
|-------------------------|------|-----|-----|----------|------------|---------------|-----------|-----------|--|--|---|--|--|-------------------------|--|
| | Base | Ply | Cap | Flashing | Protection | Fiber Glass | Polyester | Composite | Hot Asphalt  | Cold Adhesive  | Heat Weld  | Self-Adhering  | Mechanically Fastened  | | |
| DynaWeld™ Base | X | | | | | X | | | | | X | | | D 6163, Type I, Grade S | 100 ft ² (9.29 m ²) |
| DynaWeld™ Cap | | | X | | | X | | | | | X | | | D 6163, Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaWeld™ Cap FR | | | X | | | X | | | | | X | | | D 6163, Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaWeld™ Cap FR CR | | | X | | | X | | | | | X | | | D 6163, Type I, Grade G | 100 ft ² (9.29 m ²) |
| DynaWeld™ 180 S | X | | | | | | X | | | | X | | X | D 6164 Type I, Grade S | 100 ft ² (9.29 m ²) |
| DynaWeld™ 250 S | X | | | | | | X | | | | X | | X | D 6164 Type II, Grade S | 100 ft ² (9.29 m ²) |
| DynaWeld™ Cap 180 FR | | | X | | | | X | | | | X | | | D 6164 Type II, Grade G | 100 ft ² (9.29 m ²) |
| DynaWeld™ Cap 180 FR CR | | | X | | | | X | | | | X | | | D 6164 Type II, Grade G | 100 ft ² (9.29 m ²) |
| DynaWeld™ Cap 250 FR | | | X | | | | X | | | | X | | | D 6164 Type II, Grade G | 100 ft ² (9.29 m ²) |
| DynaWeld™ Cap 250 FR CR | | | X | | | | X | | | | X | | | D 6164 Type II, Grade G | 100 ft ² (9.29 m ²) |
| DynaPly® T1 HW | X | | | | | | | X | | | X | | | D 6162 Type I, Grade S | 100 ft ² (9.29 m ²) |
| DynaKap® FR T1 HW | | | X | | | | | X | | | X | | | D 6162 Type I, Grade G | 100 ft ² (9.29 m ²) |