



ASTM		Product	Use				Reinforcement			Application		Roll Coverage	Roll Weight		
			Base	Ply	Cap	Flashing	Fiber Glass	Polyester	Composite	 Cold Adhesive	 Heat Weld				
D 6222	Type I	Grade S	APPEX® 4S		X	X	X		X			X	95.8 ft² (8.9 m²)	100 lb (45.4 kg)	
			APPeX® 4S Embossed		X	X	X		X			X		89 lb (39.9 kg)	
		Grade G	APPEX® 4.5M			X	X		X					X	112 lb (50.8 kg)
			APPeX® 4.5M CR G			X	X		X					X	108 lb (49 kg)
			APPEX® 4.5M FR			X	X		X					X	112 lb (50.8 kg)
			APPeX® 4.5M FR CR G			X	X		X					X	108 lb (49 kg)
			DIBITEN			X	X		X					X	89 lb (39.9 kg)
			DIBITEN Poly/4.5 CR G			X	X		X					X	108 lb (49 kg)
D 6223	Type I	Grade S	BICOR S	X	X				X	X	X	99.5 ft² (9.2 m²)	98 lb (44.5 kg)		
		Grade G	BICOR M FR			X	X		X	X	X		111 lb (50.3 kg)		
	Type II	Grade S	TRICOR™ S	X	X				X	X	X		94 lb (42.6 kg)		
		Grade G	TRICOR™ M FR			X	X		X	X	X		117 lb (53 kg)		
			TRICOR™ M FR CR G			X	X		X	X	X		117 lb (53 kg)		
		D 6509	JM APP™ Base Sheet		X	X			X				X	X	145.08 ft² (13.5 m²)
JM APP™ Base 2.0 SQ			X	X			X				X	198.91 ft² (18.6 m²)	101 lb (45.8 kg)		
JM APP™ Base Plus			X	X			X			X	X	145.08 ft² (13.5 m²)	123 lb (55.8 kg)		
	ValuWeld® G Cold				X	X		X		X		95.8 ft² (8.9 m²)	114 lb (51.71 kg)		
	ValuWeld® S Cold			X	X	X		X		X			98 lb (44.45 kg)		