



## Adhesives and Cements

Product	Use	Description	Size	Standard
Asphalt Primer	Primer	Thin, cut-back asphalt primer used to prepare porous roof surfaces to receive hot asphalt and enhance adhesion.	4.75 gal (17.9 l) can	ASTM D 41, Type II
Urethane Insulation Adhesive	Insulation Adhesive	A one-part, cold-applied adhesive for bonding insulations to almost any roofing substrate and insulation to insulation.	1 gal (3.78 l) can	None
JM Two-Part Urethane Insulation Adhesive	Insulation Adhesive	A two-component, polyurethane adhesive used for attaching insulation boards to the roof deck or to other insulation boards.	Cartridges - 4/Case 5 gal (18.9 l) box	None
JM Green Two-Part Urethane Insulation Adhesive	Insulation Adhesive	A two-component, low-VOC, plant-based adhesive used for attaching insulation boards to the roof deck or to other insulation boards.	Cartridges - 4/Case 5 gal (18.9 l) box	None
BUR Adhesive	Membrane Adhesive	A one-part, cold application adhesive for use with built-up roofing membranes.	5 gal (18.9 l) can	None
MBR® Bonding Adhesive	Insulation/Membrane Adhesive	A two-component, cold application adhesive for use with SBS modified bitumen and roofing insulation products.	Approx. 5 gal (18.9 l) can	None
MBR® Cold Application Adhesive	Membrane Adhesive	A one-part, elastomeric interply adhesive for use with modified bitumen systems and BUR base sheets.	5 gal (18.9 l) can	None
MBR® Utility Cement	Flashing Cement	A one-part, trowelling grade, elastomeric adhesive for use as a utility adhesive with SBS modified bitumen and BUR systems.	5 gal (18.9 l) can	None
MBR® Flashing Cement	Flashing Cement	A two-part, urethane-based, trowelling grade, elastomeric adhesive for use with SBS modified bitumen and BUR flashing.	Approx. 4½ gal (17.0 l) can	None
Bestile™ Industrial Roof Cement	Flashing Cement	Medium to heavy troweling, cut-back asphalt mastic reinforced with non-asbestos fibers and special mineral stabilizers for general use in BUR systems.	4.75 gal (17.9 l) can	ASTM D 4586, Type I
PermaFlash™ Primer		Please refer to Section 2g "Liquid-Applied Systems"		
PermaFlash™ Scrim		Please refer to Section 2g "Liquid-Applied Systems"		
SA Primer	Primer	SA Primer – An SBS synthetic rubber, resin and solvent-based primer used to enhance the adhesion of self-adhering membranes on porous decks.	4.75 gal (17.9 l) pail	None
SA Primer Low VOC	Primer	SA Primer Low VOC – An SBS synthetic rubber and resin primer used to enhance the adhesion of self-adhering membranes on porous decks.	4.75 gal (17.9 l) pail	None