



Fasteners and Plates

Product	Description	System(s) [†]		Attachment*			Deck	Size	Color	Pkg
		SP	Bit	In	Ba	Me				
UltraFast® Fastener	#12 case-hardened steel, polymer-coated fastener. Available in ¼" (6 mm) hex or #3 Phillips head. Compatible with UltraFast Metal Round or Square plates and UltraFast Plastic Locking Plate.	x	x	x			Metal (18 to 26 ga.), Wood	1½" to 8" (41 mm to 203 mm)	Blue	1,000/pail (1) #3 Phillips bit/pail (1) ¼" (6 mm) hex head bit/3 pails
UltraFast® Plate (Metal)	Recessed round or square flat-bottomed plate. Compatible with UltraFast and All Purpose Fasteners.	x	x	x				3" (76 mm) round or square	Grey	1,000/pail
UltraFast® Plate (Locking Plastic)	High strength polypropylene plates with a special locking feature. Compatible with UltraFast and All Purpose Fasteners.	x	x	x				3" (76 mm) round	Blue	1,000/pail
UltraFast Pre-Assembled Fasteners with Plates	Pre-assembled fastener and plate. #12 case-hardened, polymer-coated steel. #3 Phillips head or ¼" (6 mm) hex head (special order only). Metal recessed round plate or round plastic locking plate.	x	x	x			Metal (18 to 26 ga.), Wood	Fastener: 1½" to 8" (41 mm to 203 mm) Plate: 3" (76 mm) round	Blue (Fastener only)	Quantities vary by fastener length. Bit provided in each box.
UltraFast® AccuTrac™ Fastener and Plate System	AccuTrac tool positions UltraFast Fastener and UltraFast AccuTrac metal plate in a one-step process. UltraFast AccuTrac Plates are specifically designed for use with the AccuTrac tool. Plates are available in flat-bottom or recessed designs. Standard UltraFast plates are not compatible with the AccuTrac Tool.	x	x	x			Metal (18 to 26 ga.)	Fastener: 1½" to 6" (41 mm to 152 mm) lengths Plate: 3" (76 mm) square	Blue (Fastener only)	Fasteners: 1,000/pail Plates: 1,000/pail
UltraLok™ Locking Impact Fastener	Pre-assembled Galvalume-coated steel tube and disc with a high-tensile steel wire locking staple.	x	x	x	x		Cementitious Wood Fiber, Lightweight Concrete, Gypsum	Fastener: 1.4" to 4.8" (36 mm to 122 mm) lengths Plate: 2.7" (69 mm)		1.4" to 3.8" - 500/carton 4.8" - 250/carton
Lightweight Concrete Base Sheet Pre-Assembled Fastener and Plate	Pre-assembled fastener and plate. Twin-legged, expanding fastener with Galvalume-coated steel plate.		x		x		Lightweight Concrete, Gypsum	Fastener: 1.2" (31 mm) and 1.7" (43 mm) lengths Plate: 2.7" (69 mm) round	Black	1.2" - 1,000/box 1.7" - 500/box
Polymer Auger - Fastener with Plates	Glass-reinforced, nylon fastener with an internal ¼" (6 mm) square drive and 1" (25 mm) diameter head. Each fastener comes with either a 2" (51 mm) barbed-plate design to grip membrane or a 3" (76 mm) square plate designed to lock onto Polymer Auger fastener head. Not pre-assembled.	x	x	x		x	Cementitious Wood Fiber, Gypsum	Fastener: 2½" to 7" lengths Plate: 2" (51 mm) round and 3" (76 mm) square	Black	Fastener: 500/pail Plate: 1,000/pail

[†] System(s): SP = Single Ply; Bit = Bituminous

* Attachment: In = Insulation; Ba = Base Sheet; Me = Membrane



Fasteners and Plates

Product	Description	System(s) [†]		Attachment*			Deck	Size	Color	Pkg
		SP	Bit	In	Ba	Me				
Structural Concrete Deck Fasteners	#14, knurled-thread, hammer-in, flat-head fastener with a premium coating. Compatible with UltraFast round, flat-bottomed metal plates.	x	x	x		x	Structural Concrete	2½" to 10" (64 mm to 254 mm) lengths	Black	2½"-8" - 500/pail 9"-10" - 250/pail
Zinc Nail-In Anchor	Zinc-plated steel pin. Designed to attach termination bar. Pre-drilling required. Please contact your JM sales representative for information regarding this product.	x				x	Concrete wall, Masonry wall	¼" (6 mm) dia., 1¼" (32 mm) length		1,000/pail
Anchor Disc	Round plate used for single ply membrane termination. Compatible with All Purpose and High Load Fasteners. <i>No data sheet is currently available.</i> Please contact your JM sales representative for information regarding this product.	x				x		2" (51 mm) round		1,000/box
High Load Fasteners	#15 fastener with a #3 Phillips head. Compatible with High Load, APB, Anchor Disc, and Rhino-Plate. For use in the High Load Reel-Fast Plate System and High Load AccuSeam Plate System.	x	x			x	Metal (18 to 26 ga.), Wood	1¼" (32 mm), 2" to 24" (51 mm to 610 mm) lengths	Blue	Quantities vary by fastener length.
High Load Plates	20-gauge (0.9 mm) Galvalume-coated steel discs with eye hooks. Compatible with High Load Fasteners	x					Metal (18 to 26 ga.), Wood	2⅞" (60 mm) round		1,000/pail
High Load Pre-Assembled Fasteners and Plates	Pre-assembled fastener and plate. #15 fasteners with a #3 Phillips head. 20-gauge (0.9 mm) Galvalume-coated steel disc with eye hooks.	x				x	Metal (18 to 26 ga.), Wood	Fastener: 2" to 8" (51 mm to 203 mm) lengths Plates: 2⅞" (60 mm) round	Blue	Quantities vary by fastener length. Bit provided in each plastic pail.
JM Termination Systems	Roll-formed, pre-punched aluminum strips with round, Galvalume-coated steel discs, galvanized anchors and polymer-coated fasteners.	x				x	Metal (18 to 26 ga.)	Termination Bar: 1.35" x 10' (34 mm x 3.05 m) strips Anchor Disc: 2" (51 mm) diameter Fastener: 1¼" (32 mm) Nail-In Anchor: 1¼" (32 mm)		Termination Bar: 500/tube Anchor Disc: 1,000/box Fastener: 1,000/pail Nail-In Anchor: 1,000/box

[†] System(s): SP = Single Ply; Bit = Bituminous

* Attachment: In = Insulation; Ba = Base Sheet; Me = Membrane