

Use	Product	Description	Size	Material ID	Colors	Packaging
Membrane and Flashing Accessories	Protective Stone Mat	Nominal 6.0 oz/yd ² (140 g/m ²) UV-resistant polypropylene, needle-punched fabric used as a slipsheet between membrane and ballast or pavers.	15' x 300' (4.57 m x 91.44 m)	70000100	Black	1 roll
	Seam Tape Plus	Self-adhering, cured EPDM rubber seam tape with a clear polyethylene release line for splicing EPDM sheets.	3" x 100' (7.62 cm x 30.48 m) 6" x 100' (15.24 cm x 30.48 m)	70001631 70001632	Black	3" - 4 rolls/box 6" - 2 rolls/box
Peel & Stick Membrane and Flashing Accessories	Flashing	Uncured EPDM sheet with a factory laminated, self-adhering EPDM/butyl tape for corners and projections.	6" x 100' (15.24 cm x 30.48 m) 9" x 50' (22.86 cm x 15.24 m) 12" x 50' (30.48 cm x 15.24 m)	70004127 70004128 70004129	Black	6" - 2 rolls/box 9" - 1 roll/box 12" - 1 roll/box
	Sealing Strip	Cured EPDM strip with factory laminated, self-adhering seam tape to strip in flashing details or field seams.	6" x 100' (15.24 cm x 30.48 m) 9" x 100' (22.86 cm x 30.48 m) 12" x 100' (30.48 cm x 30.48 m)	70004124 70004125 70004126	Black	6" - 2 rolls/box 9" - 1 roll/box 12" - 1 roll/box
	RTS with Tape	Polyester scrim reinforced, cured EPDM strip with a factory-laminated, 3" (80 mm) self-adhering seam tape for securing membranes at perimeters and penetrations.	6" x 100' (15.24 cm x 30.48 m)	70002742	Black	2 rolls/box
	T-Joint Patches	Uncured EPDM sheets with a factory laminated, self-adhering EPDM/Butyl tape for use where seam laps intersect perimeter or header sheets.	6" (15.24 cm) round	70004211	Black	100 patches/box
	Inside/Outside Corners	Uncured flashing with a pre-applied peel and stick tape.	7" x 9" (1.75 cm x 2.25 cm)	70004212	Black	20 corners/box
	Pipe Boots	Cone-shaped, stepped pipe boot with a pressure sensitive seam tape around the bottom. For use in flashing round roof penetrations.	1" - 6" (25 mm - 15.24 cm)	70000084	Black	10 boots/box
	Pourable Sealer Pockets	One-piece, prefabricated units with a factory-laminated, pressure sensitive seam tape for use in sealing uneven penetrations.	6" (15.24 cm) diameter 2 1/2" (6.4 cm) base flange	70000093	Black	12 pockets/box
	Walkpads	Heavy duty, solid rubber pads with a 3" (7.62 cm) pre-applied tape designed to protect roofs from damaging foot traffic.	3/8" h x 30" w x 30" l	70000104	Black	50 pads/pallet
Specialty Roofing Products	Expand-0-Flash EJ/WC	Curb-to-curb or curb-to-wall expansion joint consisting of foam-supported bellows with attachment nailing flanges. Designed to manage multidirectional movement of the roofing systems.	4" - 12" (10.16 cm - 30.48 cm) Bellows 10', 50' or 100' (3.05 m, 15.24 m or 30.48 m) rolls	90000174 90000176 90000177 90000178 90000179 90000180 90000181	White or Black	10', 50' or 100' rolls (3.05 m, 15.24 m or 30.48 m)
	Metal/Membrane Flashing	Nominal 6" (15.24 cm) strip of JM EPDM membrane secured (using a patented method) to a nominal 4" (10.16 cm) wide nailing flange, Type 100G-6, galvanized steel.	Membrane - 6" (15.24 cm) w Nailing Flange - 2" - 4" (5.08 cm - 10.16 cm)	90000643	Black	100 lin ft (30.48 lin m)/carton