

| Description  | Product       | ASTM           | Thickness                            | Color | Sizes<br>Width x Length                           | Area per Roll                                     | Weight per Roll         | Specifications        |               |           | Guarantees                                     |                                  |                           |
|--|---------------|----------------|--------------------------------------|-------|---|---|-------------------------|-----------------------|---------------|-----------|--|----------------------------------|---------------------------|
|  |               |                |                                      |       |   |   |                         | Mechanically Fastened | Fully Adhered | Ballasted | Mechanically Fastened                          | Fully Adhered                    | Ballasted                 |
| Nonreinforced, fire rated EPDM for use in fully adhered and ballasted systems. For use as a flashing in some applications. | JM EPDM 45 NR | D 4637, Type I | 45 mil                               | Black | 10' x 50'<br>(3.05 m x 15.24 m)                   | 500 ft <sup>2</sup><br>(46.45 m <sup>2</sup> )    | 179 lb<br>(81.23 kg)    | N/A                   | SE4A          | SE4B      | N/A  | 5,<br>10,<br>15 yr<br>NDL        | 5,<br>10,<br>15 yr<br>NDL |
|  |               |                |                                      |       | 10' x 100'<br>(3.05 m x 30.48 m)                  | 1,000 ft <sup>2</sup><br>(92.90 m <sup>2</sup> )  | 335 lb<br>(151.75 kg)   |                       |               |           |  |                                  |                           |
|  |               |                |                                      |       | 20' x 50'<br>(6.1 m x 15.24 m)                    | 1,000 ft <sup>2</sup><br>(92.90 m <sup>2</sup> )  | 335 lb<br>(151.75 kg)   |                       |               |           |  |                                  |                           |
|  |               |                |                                      |       | 20' x 100'<br>(6.1 m x 30.48 m)                   | 2,000 ft <sup>2</sup><br>(185.81 m <sup>2</sup> ) | 659 lb<br>(299.11 kg)   |                       |               |           |  |                                  |                           |
|  |               |                |                                      |       | 30' x 100'<br>(9.14 m x 30.48 m)                  | 3,000 ft <sup>2</sup><br>(278.71 m <sup>2</sup> ) | 970 lb<br>(440.16 kg)   |                       |               |           |  |                                  |                           |
|  |               |                |                                      |       | 40' x 100'<br>(12.19 m x 30.48 m)                 | 4,000 ft <sup>2</sup><br>(371.61 m <sup>2</sup> ) | 1,281 lb<br>(581.22 kg) |                       |               |           |  |                                  |                           |
|  | JM EPDM 60 NR |                | 10' x 50'<br>(3.05 m x 15.24 m)      |       | 500 ft <sup>2</sup><br>(46.45 m <sup>2</sup> )    | 212 lb<br>(96.16kg)                               | N/A                     | SE6A                  | SE6B          | N/A       | 5,<br>10,<br>15,<br>20 yr<br>NDL               | 5,<br>10,<br>15,<br>20 yr<br>NDL |                           |
|  |               |                | 10' x 100'<br>(3.05 m x 30.48 m)     |       | 1,000 ft <sup>2</sup><br>(92.90 m <sup>2</sup> )  | 407 lb<br>(184.61 kg)                             |                         |                       |               |           |  |                                  |                           |
|  |               |                | 16' 8" x 100'<br>(5.08 m x 30.48 m)* |       | 1,667 ft <sup>2</sup><br>(154.84 m <sup>2</sup> ) | 715 lb<br>(324.32 kg)                             |                         |                       |               |           |  |                                  |                           |
|  |               |                | 20' x 50'<br>(6.1 m x 15.24 m)       |       | 1,000 ft <sup>2</sup><br>(92.90 m <sup>2</sup> )  | 406 lb<br>(184.16 kg)                             |                         |                       |               |           |  |                                  |                           |
|  |               |                | 20' x 100'<br>(6.1 m x 30.48 m)      |       | 2,000 ft <sup>2</sup><br>(185.81 m <sup>2</sup> ) | 812 lb<br>(368.32 kg)                             |                         |                       |               |           |  |                                  |                           |
|  |               |                | 30' x 100'<br>(9.14 m x 30.48 m)     |       | 3,000 ft <sup>2</sup><br>(278.71 m <sup>2</sup> ) | 1,170 lb<br>(530.70 kg)                           |                         |                       |               |           |  |                                  |                           |
|  | JM EPDM 90 NR |                | 10' x 50'<br>(3.05 m x 15.24 m)      |       | 500 ft <sup>2</sup><br>(46.45 m <sup>2</sup> )    | 310 lb<br>(140.61 kg)                             | N/A                     | SE9A                  | SE9B          | N/A       | 5,<br>10,<br>15,<br>20,<br>25,<br>30 yr<br>NDL | 5,<br>10,<br>15,<br>20 yr<br>NDL |                           |
|  |               |                | 10' x 100'<br>(3.05 m x 30.48 m)     |       | 1,000 ft <sup>2</sup><br>(92.90 m <sup>2</sup> )  | 625 lb<br>(283.65 kg)                             |                         |                       |               |           |  |                                  |                           |

|  |              |                 |        |       |                                  |  |                       |       |       |       |   |   |                                  |
|--|--------------|-----------------|--------|-------|----------------------------------|--|-----------------------|-------|-------|-------|---|---|----------------------------------|
| Reinforced, fire-rated EPDM for use in fully adhered, mechanically fastened and ballasted systems. | JM EPDM 45 R | D 4637, Type II | 45 mil | Black | 10' x 100'<br>(3.05 m x 30.48 m) | 1,000 ft <sup>2</sup><br>(92.90 m <sup>2</sup> ) | 303 lb<br>(137.44 kg) | SE4RM | SE4RA | SE4RB | 5,<br>10,<br>15 yr<br>NDL               | 5,<br>10,<br>15 yr<br>NDL               | 5,<br>10,<br>15 yr<br>NDL        |
|  | JM EPDM 60 R |                 | 60 mil |       | 10' x 100'<br>(3.05 m x 30.48 m) | 1,000 ft <sup>2</sup><br>(92.90 m <sup>2</sup> ) | 391 lb<br>(177.36 kg) | SE6RM | SE6RA | SE6RB | 5,<br>10,<br>15,<br>20 yr<br>NDL        | 5,<br>10,<br>15,<br>20 yr<br>NDL        | 5,<br>10,<br>15,<br>20 yr<br>NDL |
|  | JM EPDM 75 R |                 | 75 mil |       | 10' x 100'<br>(3.05 m x 30.48 m) | 1,000 ft <sup>2</sup><br>(92.90 m <sup>2</sup> ) | 492 lb<br>(223.17 kg) | SE7RM | SE7RA | SE7RB | 5,<br>10,<br>15,<br>20,<br>25 yr<br>NDL | 5,<br>10,<br>15,<br>20,<br>25 yr<br>NDL | 5,<br>10,<br>15,<br>20 yr<br>NDL |

\* No Fold