

JM TPO RhinoPlate® HIGH-WIND RATING

INDUSTRY-BEST FM RATING: 1-135



JM TPO RhinoPlate® easily handles wind uplift pressures of 135 pounds/ ft²

JM TPO REQUIRES UP TO 40% FEWER FASTENERS

than competitive induction-welded systems, saving you time and money. Our system yeilds higher wind uplift approval per square foot and reduces the potential for membrane flutter. Many installers find that installing JM RhinoPlate® requires less labor and ultimately leads to greater profits.

FEWER FASTENERS, LESS LABOR, MORE PROFITS

Compare the number of fasteners you need to lock down every SQ of your roofing surface area.



JOHNS MANVILLE 25 FASTENERS/SQUARE COMPETITOR A 37.5 FASTENERS/SQUARE

10'

APPROXIMATELY

FASTENERS

1 \$0

COMPETITOR B 43 75 FASTENERS/SOUARE

10

10'

APPROXIMATELY



Powerful wind gusts sweeping along the Atlantic shoreline and Gulf Coast are known to cause considerable damage to rooftops. Fortunately, the JM RhinoPlate® best-in-class rating of FM 1-135 helps put minds at ease. Rest assured that the JM TPO RhinoPlate® system will protect your roof as well as your reputation.