



# JM PAPERMAN

**LIQUID  
MEMBRANE  
SOLID  
INVESTMENT**

# ANY SYSTEM ANY PLACE

## JM MAKES IT HAPPEN

JM PMMA Liquid Membrane and Flashing System provides an elastomeric, monolithic roofing and waterproofing membrane ideal for a wide variety of surfaces and flashings on SBS and BUR membrane systems. For plaza decks, balconies, garden roofs, small irregularly shaped roofs or roofs with many penetrations or as a standalone membrane, JM PMMA is the premium choice.



TOP COAT  
(OPTIONAL)

FINAL COAT

FLEECE REINFORCEMENT

PRIMARY RESIN COAT

PRIMER COAT

## JM PMMA LIQUID SYSTEM

The JM PMMA Liquid Membrane and Flashing System consists of a two-component, fast-curing, polymethyl-methacrylate (JM PMMA) resin and a non-woven, chopped strand fabric reinforcement.

JM PMMA can be used as a standalone membrane system or combined with JM SBS and BUR membranes as a flashing detail membrane system.

**Both options are eligible for a 20-year Peak Advantage® Guarantee.**



## IT'S ABOUT STARTING THAT NEXT JOB SOONER



JM PMMA gets in the dry faster than any other system. A half hour, on average, before applying the next coat. We help keep the job moving.

## BENEFITS OF A LIQUID MEMBRANE



Complete monolithic membrane.

Unlike fully adhered single ply, which uses a glue to hold the membrane in place, liquid-applied membranes are the glue and the membrane.



No terminations bars, boots or caulking.

Provides better flashings for difficult details.



Easy to work with. Combines with JM roofing elements for added effectiveness.

## PRIMERS

approx. 30 – 45 min. 

### JM PMMA Primer – All-Purpose

PMMA-based

Ideal for most substrates, for both vertical and for horizontal application

### JM PMMA Primer – Metal

Non-PMMA primer

Required for any metal

## RESINS

approx. 45 min. – 1½ hr. 

### JM PMMA Resin – Summer/Winter Grade

PMMA-based resin for horizontal application

Available in white or grey

### JM PMMA Flashing Resin – Summer/Winter Grade

PMMA-based resin for vertical application

Available in white or grey

## SURFACINGS

approx. 45 min. – 1 hr. 

### JM PMMA Top Coat

Optional PMMA-based top coat for aesthetics

Combine with 14 standard colors to create a custom finish

### JM PMMA Textured Top Coat

Optional PMMA-based top coat that contains an aggregate for anti-slip

Combine with 14 standard colors to create a custom finish

### JM PMMA Color Pack

1.5 kg packs for pigmenting top coat or textured top coat

Available in: Pebble Grey, Stone Grey, Light Grey, Traffic Grey, Signal White, Traffic Black, Traffic Green, Traffic Yellow, Traffic Blue, Pale Green, Terra Cotta, Traffic Red, Window Grey, Beige

## REPAIR

approx. 45 min. 

### JM PMMA Repair Paste

PMMA-based paste for substrate repair, filling select details and for stripping in joints in insulation

## REINFORCEMENT

### JM PMMA Scrim

Polyester Scrim Available in 14" and 41" widths

## ACCESSORIES

### JM PMMA Thixo

Additive combined with top coat or field resin to increase viscosity for use in vertical application

### JM PMMA Catalyst

Reactive agent used to initiate curing of JM PMMA liquid resins and primers

### JM PMMA Cleaner

Cleaner used for reactivating membrane for tie-ins or general cleaning

### JM PMMA Detailer

PMMA based resin with fibers used as a waterproofing paste when traditional reinforced flashings are not possible

## PHYSICAL PROPERTY

STANDARD TEST METHOD FOR BITUMINOUS ROOF MEMBRANES

VALUES/UNITS

### Membrane Thickness

ASTM D 5147 section 5

90 mils (2.3 mm)

### Peak Load @ 73°F (avg.)

ASTM D 5147 section 6

70 lbf/in (12.3 kN/m)

### Elongation @ Peak Load (avg.)

ASTM D 5147 section 6

42%

### Peak Load @ 73°F (avg.)

ASTM D 412 (dumbbell)

90 lbf/in (15.8 kN/m)

### Elongation @ Peak Load (avg.)

ASTM D 412 (dumbbell)

55%

### Shore A Hardness (avg.)

ASTM D 2240

81

### Water Absorption (Method I) (24th @ 73°F [23°C])

ASTM D 570

0.41%

### Water Absorption (Method II) (24th @ 122°F [23°C])

ASTM D 570

1.57%

### Low Temperature Flexibility

ASTM D 5147 section 11

-13°F (-25°C)

### Dimensional Stability (maximum movement)

ASTM D 5147 section 10

0.063%

### Tear Strength

ASTM D 5147 section 7

107 lbf (0.5 kN)

Values based on 90 mil (2.3mm) thick reinforced PMMA membrane.



717 17th St.  
Denver, CO 80202  
(800) 922-5922  
www.jm.com/roofing



PEAK  ADVANTAGE *Johns Manville*

One-manufacturer  
full-system guarantee

Johns Manville offers one of the most comprehensive guarantees in the roofing industry. That's the advantage you can expect from a financially stable, dependable leader that has been around for over 160 years.



@JohnsManvilleRoofing



@JMRoofingSystem



Johns Manville Commercial Roofing Systems



Johns Manville Roofing Systems



@JohnsManvilleRoofing



Above it all

RS-2363 8-22 (Replaces 6-18)