

## Features and Components

- Use:** JM 3 oz Polyester Slipsheet is intended for use as a separation layer between an existing roof system and a new single ply recover system.
- Material:** 3.0 oz/yd<sup>2</sup> (102 g/m<sup>2</sup>) needle-punched, non UV-resistant polyester fabric.
- Color:** White



### Component

**A**  
Accessory

Single Ply

### Type

**PT**  
Protection

**System Compatibility** This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

| Multi-Ply | BUR |    | APP |    | SBS |    |    |    |
|-----------|-----|----|-----|----|-----|----|----|----|
|           | HA  | CA | CA  | HW | HA  | CA | HW | SA |
|           |     |    |     |    |     |    |    |    |

*Do not use in Multi-Ply systems*

| Single Ply | TPO |    | PVC |    | EPDM |    |    |
|------------|-----|----|-----|----|------|----|----|
|            | MF  | AD | MF  | AD | MF   | AD | BA |
|            |     |    |     |    |      |    |    |

*Compatible with the selected Single Ply systems above*

**Key:** HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened AD = Adhered BA = Ballasted

## Peak Advantage® Guarantee Information

| Systems                                                                                                                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approved for use in mechanically fastened single ply recover and EPDM ballasted applications over existing smooth bituminous and single ply membranes.* |

\*Contact JM Technical Services @ 800-922-5922 opt. 3 for further information and qualifying guarantee assemblies and terms.

## Installation/Application



Loose Laid

- JM 3 oz Polyester Slipsheet is installed between the existing roof and single ply membrane.
- JM 3 oz Polyester Slipsheet must be installed with a 3" minimum side lap and a 6" minimum end lap. Sheet may be tacked into place as deemed necessary.

## Packaging and Dimensions

|                   |                                             |
|-------------------|---------------------------------------------|
| Roll Size         | 130" wide x 500' long (3.3 m x 152.4 m)     |
| Coverage per Roll | 5,416 ft <sup>2</sup> (503 m <sup>2</sup> ) |
| Weight per Roll   | 150 lb (68.0 kg)                            |

## Storage

|                    |                                                                                      |
|--------------------|--------------------------------------------------------------------------------------|
| Storage Conditions | Store indoors, out of direct sunlight, in a cool, dry location prior to application. |
|--------------------|--------------------------------------------------------------------------------------|