

Features and Components

Use: A prefabricated, reinforced 60 mil JM TPO, square boot in 2" and 4" (5.08 cm and 10.16 cm) sizes for tube-flashing application. Pipe boots minimize the need for field fabrication. Custom sizes and colors are available upon request. Contact your JM representative for minimum order quantity and lead time.

Material: JM TPO 60 mil reinforced membrane, with one of the widest welding windows, that is factory fabricated into a one-piece square split-pipe boot.

Color: White



Component
A
Accessory
Single Ply
Type
FP
Penetration

System Compatibility

This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR	APP	SBS				MF	TPO				PVC				EPDM			
	HA	CA	HW	HA	CA	HW		MF	AD	SA	IW	MF	AD	IW	MF	AD	BA		
Compatible with the selected multi-ply systems above																			

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Energy and the Environment

Standard		Reflectivity	Emissivity
CRRC®	Initial	0.77	0.87
	3 Yr. Aged	0.70	0.86
CA Title 24	Pass	0.77	0.87
ENERGY STAR®	Initial	0.78	0.87
	3 Yr. Aged	0.68	■■■■■
LEED® (SRI)	Initial	101	
	3 Yr. Aged	85	
Recycled Content	Post-consumer	0%	
	Post-industrial	5%	

The LEED® Solar Reflectance Index (SRI) is calculated per ASTM E1980.

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Hot Air Weld

- Do not install JM TPO Split Square Pipe Boots in direct contact with asphalt or coal tar pitch.
- Refer to JM TPO application guides or detail drawings for instructions.

Packaging and Dimensions

Size/Round Base	2" (5.08 cm) – 16" (40.64 cm) Base 4" (10.16 cm) – 16" (40.64 cm) Base
Height	8" (20.32 cm)
Boots per Box	8
Weight per Box	2" – 7 lb (3.18 kg) 4" – 8.7 lb (3.95 kg)

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.