



Quantity:

- ___ Total LF (12'-0" pcs)
- ___ Radius Fascia LF (6'-0" pcs) (Radius: ____, Convex or Concave)
- ___ Vaulted Fascia LF (6'-0" pcs) (Radius: ____, Convex or Concave)

Standard Accessories:

- ___ Inside Mitered Corner(s) (Angle: ____)
- ___ Outside Mitered Corner(s) (Angle: ____)
- ___ End Closure(s) (___ Left, ___ Right)
- ___ End Term(s) (___ Left, ___ Right)
- ___ Sump(s) (Downspout Size: ____)
- ___ Spillout(s)

Custom Accessories: (sketches required)

Special Miters and Zees

*All Componets for installing Accessories are included.

MATERIAL:

THICKNESS:

- Pre-Finished Aluminum .040 .050 .063
- Mill Finished Aluminum .040 .050 .063
- Pre-Finished Steel 24 ga 22 ga
- Stainless Steel 24 ga 22 ga

COLOR: _____

-	C DIMENSION	H DIMENSION
-	2-1/2"	4"
-	4"	5-1/2"
-	5-1/2"	7"
-	7"	8-1/2"
-	8-1/2"	10"
-	10"	11-1/2"

ANSI/SPRI ES-1 Tested

Projects Requirement's
Horizontal Design Pressure: _____psf

Job Name: _____	Customer: _____
Job #: _____	Representative: _____
Location: _____	Distributor: _____

CUSTOMER APPROVAL

Authorized Signature: _____

Approved by: _____

Date: _____