

CHOPPED STRANDS : OTHER PROCESSES

Product Characteristics			Filament Diameter (µm)		Fiber Length		Resin / Polymer Type				Certificates NA	Certificates EU	Food Contact	
Tradename	Process	Sizing	NA	EU	NA	EU	PP	UP	Phenolics	Mat Binders				
StarStran®	Carding/Needling	991	16	13	51, 102 mm	51 mm	•							
	BMC		264		14		6, 12 mm		•					•
			582		13.5		6, 12 mm		•					
			706C	16		1/8", 1/4", 1/2"			•					
			860		15		6, 12 mm		•					
			862		10.5, 15		4.5, 6, 12 mm		•					
	D-LFT	739	16		1/2"		•							
	GMT		413	16		1/2"		•						
		423	13, 16		1/2"		•							
ThermoFlow®	Extrusion/Kneading	701		13		4mm			•					
Chop-Pak®	Wet dispersible (nonwoven mat)	117	11, 13, 16		1/4", 1/2", 3/4", 1"					•				
		137	11, 13, 16		1/4", 1/2", 3/4", 1 1/4"					•				
DuraCore®	Gypsum	300	13, 16	16	1/4", 1/2"	12 mm					UL	UL		
		301		16		6 mm								

The table provides only a guideline within JM product range. For specific questions, please ask a JM representative or send mail to fibers@jm.com.

The Food Contact compliance for Europe (> 2016) is based on the requirements of the Commission Regulation (EU) 10/2011 on plastic materials and articles intended to come into contact with food.