

CHOPPED STRANDS : OTHER PROCESSES

Product Characteristics			Filament Diameter (μm)		Fiber Length		Resin / Polymer Type			Certificates NA	Certificates EU	
Tradename	Process	Sizing	NA	EU	NA	EU	PP	UP	Mat Binders			
StarStran®	Carding/Needling	991	16	13	51, 102 mm		•					
	BMC	264		14		6, 12 mm			•			
		582		13.5		6, 12 mm			•			
		860		15		6, 12 mm			•			
		862		10.5, 15		4.5, 6, 12 mm			•			
		706C	16			1/8", 1/4", 1/2"			•			
	D-LFT	738	16			1/2"		•				
		739	16			1/2"		•				
	GMT	423	13			1/2"		•				
		413	16			1/2"		•				
Chop-Pak®	Wet dispersible (nonwoven mat)	117	11, 13, 16		1/4", 1/2", 3/4", 1"				•			
		137	11, 13, 16		1/4", 1/2", 3/4", 1 1/4"				•			
		137 Opt	16		1 1/4"				•			
		199		8, 10, 11, 13		6, 9, 12 mm				•		
		141		13, 16		18, 32 mm				•		
DuraCore®	Gypsum	300	13, 16	16	1/4", 1/2"					UL	UL	
		301		16		6 mm						
		193	16			1/2"						

The table provides only a guideline within JM product range. For specific questions, please ask a JM representative or send mail to fibers@jm.com.