

SECTIONAL PIPE INSULATION - SINGLE LAYER

| I.D. Pipe Size in. mm | | 1" Thick | | | | 1½" Thick | | | | 2" Thick | | | | 2½" Thick | | | |
|--------------------------|-----|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|
| | | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton |
| ½ | 15 | 96 | 0.183 | 6.59 | 43 | 54 | 0.231 | 7.14 | 47 | 48 | 0.280 | 9.09 | 63 | 27 | 0.280 | 9.09 | 54 |
| ¾ | 20 | 96 | 0.183 | 6.59 | 42 | 54 | 0.231 | 7.14 | 45 | 48 | 0.280 | 9.09 | 61 | 27 | 0.280 | 9.09 | 56 |
| 1 | 25 | 75 | 0.190 | 6.65 | 47 | 54 | 0.264 | 8.87 | 56 | 27 | 0.190 | 6.65 | 42 | 27 | 0.280 | 9.09 | 55 |
| 1¼ | 32 | 75 | 0.190 | 6.65 | 40 | 48 | 0.280 | 9.09 | 55 | 27 | 0.190 | 6.65 | 39 | 27 | 0.280 | 9.09 | 51 |
| 1½ | 40 | 54 | 0.231 | 7.14 | 36 | 48 | 0.280 | 9.09 | 52 | 27 | 0.280 | 9.09 | 52 | 24 | 0.285 | 10.48 | 68 |
| 2 | 50 | 54 | 0.264 | 8.87 | 43 | 27 | 0.190 | 6.65 | 36 | 27 | 0.280 | 9.09 | 54 | 24 | 0.285 | 10.48 | 65 |
| 2½ | 65 | 48 | 0.280 | 9.09 | 43 | 27 | 0.280 | 9.09 | 51 | 24 | 0.285 | 10.48 | 60 | 12 | 0.190 | 6.65 | 42 |
| 3 | 80 | 27 | 0.190 | 6.65 | 30 | 27 | 0.280 | 9.09 | 46 | 24 | 0.285 | 10.48 | 57 | 12 | 0.190 | 6.65 | 38 |
| 3½ | 90 | 27 | 0.280 | 9.09 | 45 | 24 | 0.285 | 10.48 | 54 | 12 | 0.190 | 6.65 | 38 | 12 | 0.280 | 9.09 | 46 |
| 4 | 100 | 27 | 0.280 | 9.09 | 39 | 24 | 0.285 | 10.48 | 49 | 12 | 0.190 | 6.65 | 34 | 12 | 0.280 | 9.09 | 41 |
| 4½ | 115 | 24 | 0.285 | 10.48 | 46 | 12 | 0.190 | 6.65 | 33 | 12 | 0.280 | 9.09 | 42 | 6 | 0.160 | 5.78 | 28 |
| 5 | 125 | 24 | 0.285 | 10.48 | 39 | 12 | 0.190 | 6.65 | 31 | 12 | 0.280 | 9.09 | 40 | 6 | 0.160 | 5.78 | 27 |
| 6 | 150 | 12 | 0.190 | 6.65 | 24 | 12 | 0.280 | 9.09 | 32 | 6 | 0.160 | 5.78 | 25 | 6 | 0.161 | 6.08 | 29 |
| 7 | 175 | 12 | 0.280 | 9.09 | 26 | 12 | 0.232 | 7.69 | 39 | 6 | 0.161 | 6.08 | 26 | 6 | 0.190 | 6.65 | 31 |
| 8 | 200 | - | - | - | - | 12 | 0.265 | 9.19 | 39 | 6 | 0.190 | 6.65 | 28 | 6 | 0.202 | 7.63 | 35 |
| 9 | 225 | - | - | - | - | 9 | 0.264 | 8.87 | 32 | 6 | 0.190 | 6.65 | 31 | 6 | 0.280 | 9.09 | 38 |
| 10 | 250 | - | - | - | - | 6 | 0.190 | 6.65 | 27 | 6 | 0.202 | 7.63 | 35 | 6 | 0.278 | 9.31 | 42 |
| 11 | 275 | - | - | - | - | 6 | 0.202 | 7.63 | 33 | 6 | 0.280 | 9.09 | 38 | 3 | 0.160 | 5.78 | 26 |
| 12 | 300 | - | - | - | - | 6 | 0.280 | 9.09 | 34 | 6 | 0.278 | 9.31 | 41 | 3 | 0.161 | 6.08 | 27 |
| 14 | 350 | - | - | - | - | 6 | 0.278 | 9.31 | 32 | 3 | 0.161 | 6.08 | 23 | 3 | 0.183 | 6.59 | 27 |
| 15 | 375 | - | - | - | - | 3 | 0.161 | 6.08 | 20 | 3 | 0.183 | 6.59 | 25 | 3 | 0.231 | 7.14 | 28 |
| 16 | 400 | - | - | - | - | 3 | 0.183 | 6.59 | 21 | 3 | 0.231 | 7.14 | 25 | 3 | 0.232 | 7.69 | 31 |
| 17 | 425 | - | - | - | - | 3 | 0.231 | 7.14 | 21 | 3 | 0.232 | 7.69 | 26 | 3 | 0.264 | 8.87 | 31 |
| 18 | 450 | - | - | - | - | 3 | 0.232 | 7.69 | 23 | 3 | 0.247 | 7.98 | 28 | 3 | 0.265 | 9.19 | 29 |
| 19 | 475 | - | - | - | - | 3 | 0.247 | 7.98 | 23 | 3 | 0.264 | 8.87 | 28 | 3 | 0.265 | 9.19 | 33 |
| 20 | 500 | - | - | - | - | 3 | 0.264 | 8.87 | 24 | 3 | 0.265 | 9.19 | 29 | 3 | 0.285 | 10.48 | 33 |
| 21 | 525 | - | - | - | - | 3 | 0.265 | 9.19 | 24 | 3 | 0.266 | 9.51 | 29 | 1.5 | 0.247 | 7.98 | 20 |
| 22 | 550 | - | - | - | - | 3 | 0.285 | 10.48 | 25 | 3 | 0.285 | 10.48 | 30 | 1.5 | 0.264 | 8.87 | 20 |
| 23 | 575 | - | - | - | - | 3 | 0.285 | 10.48 | 26 | 1.5 | 0.264 | 8.87 | 18 | 1.5 | 0.265 | 9.19 | 20 |
| 24 | 600 | - | - | - | - | 3 | 0.285 | 10.48 | 27 | 1.5 | 0.265 | 9.19 | 19 | 1.5 | 0.266 | 9.51 | 23 |

Items in reverse print indicate factory nested /double layer.

SECTIONAL PIPE INSULATION - SINGLE LAYER (CONT'D)

| I.D. Pipe Size in. mm | | 3" Thick | | | | 3½" Thick | | | | 4" Thick | | | | 4½" Thick | | | |
|--------------------------|-----|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|
| | | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton |
| ½ | 15 | 15 | 0.202 | 7.63 | 47 | 12 | 0.190 | 6.65 | 46 | 12 | 0.280 | 9.09 | 52 | - | - | - | - |
| ¾ | 20 | 15 | 0.202 | 7.63 | 47 | 12 | 0.190 | 6.65 | 47 | 12 | 0.280 | 9.09 | 52 | - | - | - | - |
| 1 | 25 | 15 | 0.202 | 7.63 | 46 | 12 | 0.190 | 6.65 | 45 | 12 | 0.280 | 9.09 | 54 | - | - | - | - |
| 1¼ | 32 | 15 | 0.202 | 7.63 | 55 | 12 | 0.280 | 9.09 | 51 | 12 | 0.280 | 9.09 | 54 | - | - | - | - |
| 1½ | 40 | 12 | 0.190 | 6.65 | 44 | 12 | 0.280 | 9.09 | 50 | 6 | 0.160 | 5.78 | 35 | - | - | - | - |
| 2 | 50 | 12 | 0.190 | 6.65 | 42 | 12 | 0.280 | 9.09 | 48 | 6 | 0.160 | 5.78 | 31 | - | - | - | - |
| 2½ | 65 | 12 | 0.280 | 9.09 | 50 | 6 | 0.160 | 5.78 | 32 | 6 | 0.161 | 6.08 | 36 | - | - | - | - |
| 3 | 80 | 12 | 0.280 | 9.09 | 48 | 6 | 0.160 | 5.78 | 32 | 6 | 0.161 | 6.08 | 37 | - | - | - | - |
| 3½ | 90 | 6 | 0.160 | 5.78 | 30 | 6 | 0.161 | 6.08 | 36 | 6 | 0.231 | 7.14 | 40 | - | - | - | - |
| 4 | 100 | 6 | 0.160 | 5.78 | 28 | 6 | 0.161 | 6.08 | 34 | 6 | 0.231 | 7.14 | 38 | - | - | - | - |
| 4½ | 115 | 6 | 0.161 | 6.08 | 32 | 6 | 0.231 | 7.14 | 38 | 6 | 0.265 | 9.19 | 41 | - | - | - | - |
| 5 | 125 | 6 | 0.161 | 6.08 | 31 | 6 | 0.231 | 7.14 | 37 | 6 | 0.265 | 9.19 | 45 | - | - | - | - |
| 6 | 150 | 6 | 0.231 | 7.14 | 34 | 6 | 0.265 | 9.19 | 40 | 6 | 0.266 | 9.51 | 47 | 6 | 0.290 | 11.30 | 54 |
| 7 | 175 | 6 | 0.202 | 7.63 | 39 | 6 | 0.280 | 9.09 | 40 | 6 | 0.290 | 11.30 | 46 | 3 | 0.161 | 6.08 | 30 |
| 8 | 200 | 6 | 0.280 | 9.09 | 41 | 6 | 0.290 | 11.30 | 50 | 3 | 0.161 | 6.08 | 34 | 3 | 0.161 | 6.08 | 39 |
| 9 | 225 | 6 | 0.278 | 9.31 | 48 | 3 | 0.160 | 5.78 | 30 | 3 | 0.161 | 6.08 | 32 | 3 | 0.183 | 6.59 | 36 |
| 10 | 250 | 3 | 0.160 | 5.78 | 29 | 3 | 0.161 | 6.08 | 33 | 3 | 0.183 | 6.59 | 38 | 3 | 0.231 | 7.14 | 41 |
| 11 | 275 | 3 | 0.161 | 6.08 | 30 | 3 | 0.183 | 6.59 | 30 | 3 | 0.231 | 7.14 | 38 | 3 | 0.247 | 7.98 | 40 |
| 12 | 300 | 3 | 0.183 | 6.59 | 28 | 3 | 0.231 | 7.14 | 32 | 3 | 0.247 | 7.98 | 39 | 3 | 0.265 | 9.19 | 42 |
| 14 | 350 | 3 | 0.231 | 7.14 | 32 | 3 | 0.232 | 7.69 | 37 | 3 | 0.265 | 9.19 | 41 | 3 | 0.265 | 9.19 | 46 |
| 15 | 375 | 3 | 0.232 | 7.69 | 32 | 3 | 0.264 | 8.87 | 36 | 3 | 0.265 | 9.19 | 40 | 3 | 0.266 | 9.51 | 46 |
| 16 | 400 | 3 | 0.264 | 8.87 | 35 | 3 | 0.265 | 9.19 | 39 | 3 | 0.265 | 9.51 | 45 | 3 | 0.290 | 11.30 | 43 |
| 17 | 425 | 3 | 0.265 | 9.19 | 37 | 3 | 0.266 | 9.51 | 42 | 3 | 0.285 | 10.48 | 44 | 1.5 | 0.247 | 7.98 | 28 |
| 18 | 450 | 3 | 0.266 | 9.51 | 36 | 3 | 0.285 | 10.48 | 39 | 1.5 | 0.247 | 7.98 | 27 | 1.5 | 0.264 | 8.87 | 29 |
| 19 | 475 | 3 | 0.285 | 10.48 | 38 | 1.5 | 0.247 | 7.98 | 22 | 1.5 | 0.264 | 8.87 | 25 | 1.5 | 0.265 | 9.19 | 28 |
| 20 | 500 | 1.5 | 0.247 | 7.98 | 21 | 1.5 | 0.264 | 8.87 | 24 | 1.5 | 0.265 | 9.19 | 29 | 1.5 | 0.266 | 9.51 | 33 |
| 21 | 525 | 1.5 | 0.264 | 8.87 | 22 | 1.5 | 0.265 | 9.19 | 25 | 1.5 | 0.266 | 9.51 | 28 | 1.5 | 0.285 | 10.48 | 30 |
| 22 | 550 | 1.5 | 0.265 | 9.19 | 22 | 1.5 | 0.266 | 9.51 | 25 | 1.5 | 0.285 | 10.48 | 28 | 1.5 | 0.161 | 6.08 | 31 |
| 23 | 575 | 1.5 | 0.266 | 9.51 | 25 | 1.5 | 0.285 | 10.48 | 27 | 1.5 | 0.161 | 6.08 | 28 | 1.5 | 0.161 | 6.08 | 31 |
| 24 | 600 | 1.5 | 0.285 | 10.48 | 24 | 1.5 | 0.161 | 6.08 | 28 | 1.5 | 0.161 | 6.08 | 31 | 1.5 | 0.161 | 6.08 | 35 |

Items in reverse print indicate factory nested /double layer.

SECTIONAL PIPE INSULATION - SINGLE LAYER (CONT'D)

| I.D. Pipe Size in. mm | | 5" Thick | | | | 5½" Thick | | | | 6" Thick | | | |
|--------------------------|-----|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|
| | | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton |
| ½ | 15 | - | - | - | - | - | - | - | - | - | - | - | - |
| ¾ | 20 | - | - | - | - | - | - | - | - | - | - | - | - |
| 1 | 25 | - | - | - | - | - | - | - | - | - | - | - | - |
| 1¼ | 32 | - | - | - | - | - | - | - | - | - | - | - | - |
| 1½ | 40 | - | - | - | - | - | - | - | - | - | - | - | - |
| 2 | 50 | - | - | - | - | - | - | - | - | - | - | - | - |
| 2½ | 65 | - | - | - | - | - | - | - | - | - | - | - | - |
| 3 | 80 | - | - | - | - | - | - | - | - | - | - | - | - |
| 3½ | 90 | - | - | - | - | - | - | - | - | - | - | - | - |
| 4 | 100 | - | - | - | - | - | - | - | - | - | - | - | - |
| 4½ | 115 | - | - | - | - | - | - | - | - | - | - | - | - |
| 5 | 125 | - | - | - | - | - | - | - | - | - | - | - | - |
| 6 | 150 | 3 | 0.161 | 6.08 | 32 | 3 | 0.161 | 6.08 | 36 | 3 | 0.183 | 6.59 | 39 |
| 7 | 175 | 3 | 0.161 | 6.08 | 33 | 3 | 0.183 | 6.59 | 35 | 3 | 0.160 | 5.78 | 45 |
| 8 | 200 | 3 | 0.183 | 6.59 | 42 | 3 | 0.231 | 7.14 | 45 | 3 | 0.247 | 7.98 | 44 |
| 9 | 225 | 3 | 0.231 | 7.14 | 41 | 3 | 0.247 | 7.98 | 43 | 3 | 0.265 | 9.19 | 44 |
| 10 | 250 | 3 | 0.247 | 7.98 | 41 | 3 | 0.265 | 9.19 | 45 | 3 | 0.265 | 9.19 | 49 |
| 11 | 275 | 3 | 0.265 | 9.19 | 45 | 3 | 0.265 | 9.19 | 47 | 3 | 0.266 | 9.51 | 48 |
| 12 | 300 | 3 | 0.265 | 9.19 | 47 | 3 | 0.266 | 9.51 | 49 | 3 | 0.285 | 10.48 | 51 |
| 14 | 350 | 3 | 0.266 | 9.51 | 49 | 3 | 0.290 | 11.30 | 49 | 1.5 | 0.247 | 7.98 | 30 |
| 15 | 375 | 3 | 0.290 | 11.30 | 48 | 1.5 | 0.247 | 7.98 | 30 | 1.5 | 0.264 | 8.87 | 30 |
| 16 | 400 | 1.5 | 0.247 | 7.98 | 27 | 1.5 | 0.264 | 8.87 | 31 | 1.5 | 0.265 | 9.19 | 31 |
| 17 | 425 | 1.5 | 0.264 | 8.87 | 29 | 1.5 | 0.265 | 9.19 | 32 | 1.5 | 0.266 | 9.51 | 33 |
| 18 | 450 | 1.5 | 0.265 | 9.19 | 28 | 1.5 | 0.266 | 9.51 | 31 | 1.5 | 0.285 | 10.48 | 35 |
| 19 | 475 | 1.5 | 0.266 | 9.51 | 31 | 1.5 | 0.285 | 10.48 | 32 | 1.5 | 0.161 | 6.08 | 35 |
| 20 | 500 | 1.5 | 0.285 | 10.48 | 34 | 1.5 | 0.161 | 6.08 | 36 | 1.5 | 0.161 | 6.08 | 36 |
| 21 | 525 | 1.5 | 0.161 | 6.08 | 33 | 1.5 | 0.161 | 6.08 | 34 | 1.5 | 0.161 | 6.08 | 37 |
| 22 | 550 | 1.5 | 0.161 | 6.08 | 34 | 1.5 | 0.161 | 6.08 | 35 | 1.5 | 0.183 | 6.59 | 38 |
| 23 | 575 | 1.5 | 0.161 | 6.08 | 35 | 1.5 | 0.183 | 6.59 | 36 | 1.5 | 0.231 | 7.14 | 40 |
| 24 | 600 | 1.5 | 0.183 | 6.59 | 36 | 1.5 | 0.231 | 7.14 | 38 | 1.5 | 0.231 | 7.14 | 42 |

SECTIONAL PIPE INSULATION - QUAD

| I.D. Pipe Size in mm | | 1½" Thick | | | | 2" Thick | | | | 2½" Thick | | | | 3" Thick | | | | 3½" Thick | | | |
|-------------------------|------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|
| | | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton |
| 25 | 625 | 3 | 0.161 | 6.08 | 25 | 3 | 0.232 | 7.69 | 32 | 1.5 | 0.160 | 5.78 | 22 | 1.5 | 0.161 | 6.08 | 24 | 1.5 | 0.161 | 6.08 | 25 |
| 26 | 650 | 3 | 0.161 | 6.08 | 28 | 3 | 0.232 | 7.69 | 32 | 1.5 | 0.160 | 5.78 | 23 | 1.5 | 0.161 | 6.08 | 27 | 1.5 | 0.161 | 6.08 | 27 |
| 27 | 675 | 3 | 0.161 | 6.08 | 29 | 3 | 0.264 | 8.87 | 34 | 1.5 | 0.161 | 6.08 | 23 | 1.5 | 0.161 | 6.08 | 26 | 1.5 | 0.183 | 6.59 | 30 |
| 28 | 700 | 3 | 0.183 | 6.59 | 29 | 3 | 0.264 | 8.87 | 34 | 1.5 | 0.183 | 6.59 | 24 | 1.5 | 0.183 | 6.59 | 26 | 1.5 | 0.231 | 7.14 | 29 |
| 29 | 725 | 3 | 0.183 | 6.59 | 29 | 3 | 0.264 | 8.87 | 36 | 1.5 | 0.231 | 7.14 | 25 | 1.5 | 0.231 | 7.14 | 27 | 1.5 | 0.231 | 7.14 | 30 |
| 30 | 750 | 3 | 0.183 | 6.59 | 31 | 3 | 0.264 | 8.87 | 38 | 1.5 | 0.231 | 7.14 | 25 | 1.5 | 0.231 | 7.14 | 28 | 1.5 | 0.232 | 7.69 | 30 |
| 31 | 775 | 3 | 0.183 | 6.59 | 32 | 3 | 0.264 | 8.87 | 39 | 1.5 | 0.231 | 7.14 | 26 | 1.5 | 0.232 | 7.69 | 26 | 1.5 | 0.232 | 7.69 | 31 |
| 32 | 800 | - | - | - | - | 3 | 0.265 | 9.19 | 39 | 1.5 | 0.232 | 7.69 | 24 | 1.5 | 0.247 | 7.98 | 28 | 1.5 | 0.264 | 8.87 | 32 |
| 33 | 825 | - | - | - | - | 3 | 0.265 | 9.19 | 41 | 1.5 | 0.247 | 7.98 | 27 | 1.5 | 0.264 | 8.87 | 30 | 1.5 | 0.265 | 9.19 | 33 |
| 34 | 850 | - | - | - | - | 3 | 0.265 | 9.19 | 38 | 1.5 | 0.265 | 9.19 | 28 | 1.5 | 0.265 | 9.19 | 29 | 1.5 | 0.265 | 9.19 | 33 |
| 35 | 875 | - | - | - | - | 3 | 0.266 | 9.51 | 43 | 1.5 | 0.266 | 9.51 | 28 | 1.5 | 0.265 | 9.19 | 31 | 1.5 | 0.266 | 9.51 | 34 |
| 36 | 900 | - | - | - | - | 3 | 0.285 | 10.48 | 42 | 1.5 | 0.266 | 9.51 | 27 | 1.5 | 0.266 | 9.51 | 31 | 1.5 | 0.266 | 9.51 | 36 |
| 37 | 925 | - | - | - | - | 3 | 0.285 | 10.48 | 45 | 1.5 | 0.285 | 10.48 | 29 | 1.5 | 0.266 | 9.51 | 33 | 1.5 | 0.290 | 11.30 | 36 |
| 38 | 950 | - | - | - | - | 1.5 | 0.290 | 11.30 | 46 | 1.5 | 0.290 | 11.30 | 30 | 1.5 | 0.290 | 11.30 | 33 | 1.5 | 0.290 | 11.30 | 36 |
| 39 | 975 | - | - | - | - | 1.5 | 0.290 | 11.30 | 27 | 1.5 | 0.290 | 11.30 | 31 | 1.5 | 0.290 | 11.30 | 34 | 1.5 | 0.290 | 11.30 | 37 |
| 40 | 1000 | - | - | - | - | 1.5 | 0.290 | 11.30 | 26 | 1.5 | 0.290 | 11.30 | 31 | 1.5 | 0.290 | 11.30 | 35 | 1.5 | 0.290 | 11.30 | 38 |
| 41 | 1025 | - | - | - | - | 1.5 | 0.390 | 13.69 | 28 | 1.5 | 0.390 | 13.69 | 32 | 1.5 | 0.390 | 13.69 | 35 | 1.5 | 0.290 | 11.30 | 38 |
| 42 | 1050 | - | - | - | - | 1.5 | 0.390 | 13.69 | 27 | 1.5 | 0.390 | 13.69 | 29 | 1.5 | 0.390 | 13.69 | 34 | 1.5 | 0.290 | 11.30 | 38 |
| 43 | 1075 | - | - | - | - | 1.5 | 0.390 | 13.69 | 27 | 1.5 | 0.390 | 13.69 | 31 | 1.5 | 0.390 | 13.69 | 32 | 1.5 | 0.290 | 11.30 | 45 |
| 44 | 1100 | - | - | - | - | 1.5 | 0.390 | 13.69 | 28 | 1.5 | 0.390 | 13.69 | 32 | 1.5 | 0.390 | 13.69 | 36 | 1.5 | 0.290 | 11.30 | 38 |

SECTIONAL PIPE INSULATION - QUAD (CONT'D)

| I.D. Pipe Size in mm | | 4" Thick | | | | 4½" Thick | | | | 5" Thick | | | | 5½" Thick | | | | 6" Thick | | | |
|-------------------------|------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|-------------------|----------------|-----------------|----------------|
| | | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton | Ln.Ft./ Carton | Load Factor | Cube/ Carton | Lbs/ Carton |
| 25 | 625 | 1.5 | 0.161 | 6.08 | 30 | 1.5 | 0.183 | 6.59 | 34 | 1.5 | 0.231 | 7.14 | 35 | 1.5 | 0.231 | 7.14 | 38 | 1.5 | 0.232 | 7.69 | 42 |
| 26 | 650 | 1.5 | 0.183 | 6.59 | 31 | 1.5 | 0.231 | 7.14 | 35 | 1.5 | 0.231 | 7.14 | 38 | 1.5 | 0.232 | 7.69 | 42 | 1.5 | 0.232 | 7.69 | 43 |
| 27 | 675 | 1.5 | 0.231 | 7.14 | 32 | 1.5 | 0.231 | 7.14 | 36 | 1.5 | 0.232 | 7.69 | 37 | 1.5 | 0.232 | 7.69 | 41 | 1.5 | 0.264 | 8.87 | 45 |
| 28 | 700 | 1.5 | 0.231 | 7.14 | 33 | 1.5 | 0.232 | 7.69 | 37 | 1.5 | 0.232 | 7.69 | 40 | 1.5 | 0.264 | 8.87 | 43 | 1.5 | 0.265 | 9.19 | 45 |
| 29 | 725 | 1.5 | 0.232 | 7.69 | 34 | 1.5 | 0.232 | 7.69 | 37 | 1.5 | 0.264 | 8.87 | 39 | 1.5 | 0.265 | 9.19 | 43 | 1.5 | 0.265 | 9.19 | 47 |
| 30 | 750 | 1.5 | 0.232 | 7.69 | 32 | 1.5 | 0.264 | 8.87 | 35 | 1.5 | 0.265 | 9.19 | 39 | 1.5 | 0.265 | 9.19 | 43 | 1.5 | 0.266 | 9.51 | 47 |
| 31 | 775 | 1.5 | 0.264 | 8.87 | 35 | 1.5 | 0.265 | 9.19 | 39 | 1.5 | 0.265 | 9.19 | 41 | 1.5 | 0.266 | 9.51 | 45 | 1.5 | 0.266 | 9.51 | 49 |
| 32 | 800 | 1.5 | 0.265 | 9.19 | 36 | 1.5 | 0.265 | 9.19 | 40 | 1.5 | 0.266 | 9.51 | 42 | 1.5 | 0.266 | 9.51 | 46 | 1.5 | 0.290 | 11.30 | 49 |
| 33 | 825 | 1.5 | 0.265 | 9.19 | 37 | 1.5 | 0.266 | 9.51 | 41 | 1.5 | 0.266 | 9.51 | 43 | 1.5 | 0.290 | 11.30 | 47 | 1.5 | 0.290 | 11.30 | 50 |
| 34 | 850 | 1.5 | 0.266 | 9.51 | 38 | 1.5 | 0.266 | 9.51 | 42 | 1.5 | 0.290 | 11.30 | 43 | 1.5 | 0.290 | 11.30 | 49 | 1.5 | 0.290 | 11.30 | 52 |
| 35 | 875 | 1.5 | 0.266 | 9.51 | 39 | 1.5 | 0.290 | 11.30 | 43 | 1.5 | 0.290 | 11.30 | 44 | 1.5 | 0.290 | 11.30 | 48 | 1.5 | 0.290 | 11.30 | 52 |
| 36 | 900 | 1.5 | 0.290 | 11.30 | 40 | 1.5 | 0.290 | 11.30 | 44 | 1.5 | 0.290 | 11.30 | 47 | 1.5 | 0.290 | 11.30 | 50 | 1.5 | 0.290 | 11.30 | 54 |
| 37 | 925 | 1.5 | 0.290 | 11.30 | 40 | 1.5 | 0.290 | 11.30 | 45 | 1.5 | 0.290 | 11.30 | 47 | 1.5 | 0.290 | 11.30 | 51 | 1.5 | 0.290 | 11.30 | 56 |
| 38 | 950 | 1.5 | 0.290 | 11.30 | 41 | 1.5 | 0.290 | 11.30 | 46 | 1.5 | 0.290 | 11.30 | 47 | 1.5 | 0.290 | 11.30 | 51 | 1.5 | 0.290 | 11.30 | 56 |
| 39 | 975 | 1.5 | 0.290 | 11.30 | 42 | 1.5 | 0.290 | 11.30 | 47 | 1.5 | 0.290 | 11.30 | 49 | 1.5 | 0.290 | 11.30 | 54 | 1.5 | 0.290 | 11.30 | 58 |
| 40 | 1000 | 1.5 | 0.290 | 11.30 | 43 | 1.5 | 0.290 | 11.30 | 45 | 1.5 | 0.290 | 11.30 | 50 | - | - | - | - | - | - | - | - |
| 41 | 1025 | 1.5 | 0.290 | 11.30 | 44 | 1.5 | 0.290 | 11.30 | 45 | 1.5 | 0.290 | 11.30 | 50 | - | - | - | - | - | - | - | - |
| 42 | 1050 | 1.5 | 0.290 | 11.30 | 41 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 43 | 1075 | 1.5 | 0.290 | 11.30 | 45 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 44 | 1100 | 1.5 | 0.290 | 11.30 | 43 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

SECTIONAL PIPE INSULATION

CARTON INFORMATION

| Load Factor | Cube/Carton | Carton Dimension (in.) | Carton No. |
|-------------|-------------|------------------------|------------|
| 0.160 | 5.78 | 22x12x36.5 | 14 |
| 0.161 | 6.08 | 24x12x36.5 | 15 |
| 0.183 | 6.59 | 24x13x36.5 | 18 |
| 0.231 | 7.14 | 26x13x36.5 | 19 |
| 0.232 | 7.69 | 26x14x36.5 | 20 |
| 0.264 | 8.87 | 28x15x36.5 | 23 |
| 0.265 | 9.19 | 29x15x36.5 | 25 |
| 0.266 | 9.51 | 30x15x36.5 | 26 |
| 0.285 | 10.48 | 31x15x36.5 | 27 |
| 0.390 | 13.69 | 36.75x18.75x36.5 | 38 |
| 0.290 | 11.30 | 32.75x16.5x36.5 | 39 |
| 0.280 | 9.09 | 20.75x20.75x36.5 | 40 |
| 0.190 | 6.65 | 17.75x17.75x36.5 | 41 |
| 0.202 | 7.63 | 19x19x36.5 | 44 |
| 0.247 | 7.98 | 27x14x36.5 | 48 |
| 0.278 | 9.31 | 21x21x36.5 | 56 |

Industrial Insulation Group, LLC manufactures MinWool-1200® mineral fiber pipe, block and a variety of other insulations; Thermo-12® Gold Calcium Silicate pipe and block insulation; Microporous Blanket Insulation; Super Firetemp® fireproofing board; SprouleWR-1200® Perlite pipe and block insulation; high-temperature adhesives, and insulating finishing cement. The physical and chemical properties presented herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Numerical flame spread and smoke developed ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions. Check with the Customer Service Office to assure current information. All Industrial Insulation Group products are sold subject to the Johns Manville Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville Limited Warranty and Limitation of Remedy, email info.industrial@jm.com.

CUSTOMER SERVICE
TECHNICAL & GENERAL INFORMATION
 (800) 866-3234



2100 LINE STREET • BRUNSWICK, GA 31520