



GoBoard® Seam Fabric



For use with GoBoard® waterproof tile backer board and shower system

GoBoard® Seam Fabric is a light weight, point-bonded polyester non-woven that is specifically designed to enhance the performance of all GoBoard products. When used with GoBoard, it increases tensile strength at the joints and provides superior adhesion between GoBoard® Pro Sealant and thin set mortars without needing to wait for the sealant to skin over.



Uses

GoBoard® Seam Fabric is specifically designed to reinforce the GoBoard line of products in tile backing applications.

Features

- Alkali resistant.
- Improved shear bond strength by over 30%.
- Increased joint strength by over 50%.
- Shortens the time to tile.

Application Instructions

1. Install GoBoard® with GoBoard® Fasteners or GoBoard® Washers per the installation instructions* making sure to leave 1/8" gaps between all boards and transitions.
2. Fill all joints with GoBoard® Pro Sealant and spread excess sealant approximately 1.5" on either of joints.
3. Cut GoBoard® Seam Fabric to required lengths using a scissors or a utility knife. Continue on with 3 steps.
4. Place strip of GoBoard Seam Fabric over wet GoBoard Pro Sealant.
5. Using a clean putty knife, set seam fabric into sealant using gentle sweeping motion. The sealant should not pass through the fabric.
6. Begin tiling.

* For detailed GoBoard Tile Backer Installation Instructions visit: <https://www.jm.com/content/dam/jm/global/en/tile-backer-boards/GB-001-GoBoard-Installation-Instructions-and-Technical-Data.pdf>



For more information visit www.jm.com/GoBoard

Property	Typical
Color	White
Weight (ASTM D3776)	40 g/m ²
Width	3"
Length	300 ft
Elongation (ASTM 4595)	
MD	21%
CD	18%
Air Permeability (GB/T5453-1997)	314 CFM (200 Pa)
Tensile Strength (ASTM D 4595)	
MD	600 lbf/in
CD	455 lbf/in
Shear Bond Strength (ANSI A118.15 7.1.3)	>50 psi